


## TSURUMI SERIA C [2/2]



|                      | <b>100C43.7</b>                              | <b>100C45.5</b> | <b>100C47.5</b> | <b>100C411</b> |
|----------------------|--|-----------------|-----------------|----------------|
| Ciecz                | ścieki i ciecze z zanieczyszczeniami stałymi |                 |                 |                |
| Wydajność [m³/h]     | 102  | 137,4           | 150             | 165            |
| Wys. podnoszenia [m] | 16,0   | 18,1            | 23,0            | 26,0           |
| Złącze wylotowe [mm] | 100  |                 |                 |                |
| Masa [kg]            | 84   | 142             | 155             | 178            |
| Przelot [mm]         | 60   | 40              | 40              | 50             |
| Wymiary (L × H) [mm] | 490 × 860                                    | 619 × 690       | 619 × 710       | 642 × 805      |
| Silnik               | elektryczny                                  |                 |                 |                |
| Moc silnika [kW]     | 3,7  | 5,5             | 7,5             | 11,0           |
| Zabezpieczenie [A]   | 8,0  | 12,1            | 15,9            | 23,8           |
| Start                | bezpośredni                                  |                 |                 |                |
| Zasilanie            | 400 V / 3-fazy / 50 Hz                       |                 |                 |                |