



TSURUMI SERIA UZ [1/2]



	50UZ41.5	80UZ42.2	100UZ43.7	80UZ45.5
Ciecz	ścieki i inne zanieczyszczone ciecze			
Wydajność [m³/h]	38,4	89,4	91,2	114
Wys. podnoszenia [m]	10,2	8,8	12,7	15
Złącze wylotowe [mm]	50	80	100	80
Masa [kg]	52	66	79	129
Przełot [mm]	50	80	100	80
Wymiary (L x H) [mm]	405 x 566	531 x 637	628 x 737	595 x 899
Silnik	elektryczny			
Moc silnika [kW]	1,5	2,2	3,7	5,5
Rozruch	D.O.L.			
Start	bezpośredni			
Zasilanie	400 V / 3-fazy / 50 Hz			

TSURUMI SERIA UZ [2/2]



	100UZ45.5	80UZ47.5	100UZ47.5	100UZ411
Ciecz	ścieki i inne zanieczyszczone ciecze			
Wydajność [m³/h]	141,6	114	150	156
Wys. podnoszenia [m]	13,2	19	15,6	19
Złącze wylotowe [mm]	100	80	100	100
Masa [kg]	145	142	158	191
Przełot [mm]	100	80	100	100
Wymiary (L x H) [mm]	652 x 939	595 x 920	652 x 960	660 x 1021
Silnik	elektryczny			
Moc silnika [kW]	5,5	7,5	7,5	11,0
Rozruch	D.O.L.		S.D.	
Start	bezpośredni			
Zasilanie	400 V / 3-fazy / 50 Hz			